(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

FK 45 FOODGRADE Component A UFI: 0MHF-UCU1-R8S9-EH24

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Industrial use Professional use Epoxy paint

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	Fakolith Farben GmbH
Address:	Carl-Benz-Str. 19
City:	D-64658 - Fürth/ Odw.
Province:	Hesse
Telephone:	+49 (0) 6253/ 2394-0
Fax:	+49 (0) 6253/ 2394-10
E-mail:	info@fakolith.com
Web:	www.fakolith.com

·Information Department:

Germany: Uwe Farenkopf (germany@fakolith.com) Tel. + 49 (0) 6253 / 2394-0 Fax: +49 (0) 6253 / 2394-10

1.4 Emergency telephone number:

Spain: +34 (0) 915 620 420 **Germany:** +49 (0) 61 31 19 240 **Austria:** +43 (0) 14 06 43 43 **Switzerland:** +41 (0) 44 25 15 151 **Italy:** +39 (0) 26 44 42 523

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects. Eye Irrit. 2 : Causes serious eye irritation. Skin Irrit. 2 : Causes skin irritation. Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022



Signal Word:

Warning

Hazard statements:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
- P321 Specific treatment (see on this label).
- P391 Collect spillage.
- P501 Dispose of contents/continaer according to local/regional/national/international legistlation.

EUH statements: EUH205

Contains epoxy constituents. May produce an allergic reaction.

Contains:

1,4-bis(2,3 epoxypropoxy)butane, butanedioldiglycidyl ether

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Active substances: Silver phosphate glass 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

The product may have the following additional risks: Prevent material from contaminating groundwater. The product should not be allowed to enter drains, pipes, or soil (soil).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification No 127	• • • •
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

Index No: 603-074- 00-8 CAS No: 25068-38-6 EC No: 500-033-5 Registration No: 01- 2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	25 - 50 %	Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
Index No: 603-072- 00-7 CAS No: 2425-79-8 EC No: 219-371-7 Registration No: 01- 2119494060-45-XXXX	1,4-bis(2,3 epoxypropoxy)butane, butanedioldiglycidyl ether	10 - 25 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 57834-33-0 EC No: 260-976-0	ethyl 4- [[(methylphenylamino)methylene]amino]benzoat e	1 - 10 %	Acute Tox. 4, H302	-
CAS No: 73038-25-2	Alcohol ethoxylate phosphate ester	1 - 3 %	Aquatic Chronic 3, H412 - Eye Dam. 1, H318 - Skin Irrit. 2, H315	-
CAS No: 1065336-91- 5 Registration No: 01- 2119491304-40-XXXX	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	0.25 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Skin Sens. 1A, H317	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



 Version 1
 Date of compilation: 27/04/2020

 Version 7 (replaces version 6)
 Revision date: 06/04/2022

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. In the application area, smoking, eating, and drinking must be prohibited. Follow legislation on occupational health and safety.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Use for direct food contact applications (Reg 10/2011)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS No: 25068-38-6 EC No: 500-033-5	DNEL (Workers)	Inhalation, Chronic, Systemic effects	12,25 (mg/m³)
1,4-bis(2,3 epoxypropoxy)butane, butanedioldiglycidyl ether CAS No: 2425-79-8 EC No: 219-371-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	1,63 (mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %	
Uses:	Industrial use Professional use	
	Epoxy paint	
Breathing protecti	ion:	
PPE:	Filter mask for protection against gases and particles.	
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.	
CEN standards:	EN 136, EN 140, EN 405	
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.	
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach rvations: the necessary filters to the equipment according to the specific nature of the risk (Particles and aeroso P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.	
ilter Type needed: A3		
Hand protection:		
PPE:	Work gloves.	
Characteristics:	«CE» marking, category I.	

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1 I Version 7 (repla	Date of compilation: 27/ aces version 6)	04/2020 Revision date:	06/04/2022	Print da	Page 6 of 12 te: 15/06/2023
CEN standards:	EN 374-1, En 374-2, El Keep in a dry place av		of heat and avoid	d exposure to sunlight as m	uch as possible
Maintenance:				esistance, or apply paints, s	
Observations:	Gloves should be of the Always use with clean,		fit the user's har	d well, not being too loose	or too tight.
Material:	Chloroprene	Breakthrough time (min.):	> 480	Material thickness (mm):	0,18
Material:	Nitrile	Breakthrough time (min.):	> 480	Material thickness (mm):	0,38
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Face shield.				
Characteristics:	«CE» marking, categor		otector against sp	lashing liquid.	
CEN standards:	EN 165, EN 166, EN 16	7, EN 168			
Maintenance: Observations:	smoothly.			ile parts move	
Skin protection	1				
PPE:	Protective clothing.				
Characteristics:	«CE» marking, categor order not to obstruct th		ng should not be	too tight or loose in	
CEN standards:	EN 340				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in				
PPE:	Work footwear.				
Characteristics:	«CE» marking, categor				
CEN standards:	EN ISO 13287, EN 203				
Maintenance:	enance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.				
Observations:	Work footwear for prof injury resulting from ar		protection eleme	nts aimed at protecting use	rs against any

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: White Odour: Soft, characteristic

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: 155 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is apolar/aprotic).

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Insoluble, immiscible

Liposolubility: Not applicable/Not available due to the nature/properties of the product Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: 1,52 Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product Explosive properties: Not applicable/Not available due to the nature/properties of the product Oxidizing properties: Not applicable/Not available due to the nature/properties of the product Dropping point: Not applicable/Not available due to the nature/properties of the product Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity; Not conclusive data for classification.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Dermal) = 7.835 mg/kg ATE (Oral) = 19.771 mg/kg

b) skin corrosion/irritation;

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A

Version 1 Date of compilation: 27/04/2020 Version 7 (replaces version 6) Revision date: 06/04/2022

Product classified: Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

11.2 Information on other hazards. Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health. Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.



(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A

Version 1 Date of compilation: 27/04/2020 chemical systems Page 9 of 12 Print date: 15/06/2023

Version 7 (replaces version 6) Revision date: 06/04/2022

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management. European waste catalogue / waste key according to waste list regulation (VeVA 814.610) 080111 : Waste n.e.c.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN3082

14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / ALCOHOL ETHOXYLATE PHOSPHATE ESTER), 9, PG III, (-)

UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: IMDG: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / ALCOHOL ETHOXYLATE PHOSPHATE ESTER), 9, PG III, MARINE POLLUTANT

UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: ICAO/IATA: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / ALCOHOL ETHOXYLATE PHOSPHATE ESTER), 9, PG III

14.3 Transport hazard class(es).

Class(es): 9

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.



(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

Dangerous for the environment Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

14.6 Special precautions for user. Labels: 9



Hazard number: 90 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end use such as floors, solvent-borne Phase I* (from 01/01/2007): 550 g/l Phase II* (from 01/01/2010): 500 g/l (*) g/l ready to use

VOC content (p/p): 0 % VOC content: 0 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

Information related to Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products: Treated article.

	Active substances				
	Silver phosphate glass				
	CAS No: 308069-39-8				
-					

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H302 H312	Harmful if swallowed. Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4 Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4 Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1A : Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Changes in the composition of the product (SECTION 3.2).
- Elimination of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Elimination of toxicity values (SECTION 11.1).
- Change in the hazard classification (SECTION 11.1).
- Elimination of ecological information values (SECTION 12.1).
- Elimination of ecological information values (SECTION 12.3).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component A



Version 1Date of compilation: 27/04/2020Version 7 (replaces version 6)Revision date: 06/04/2022

CAS No	Name	State
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	Registered12
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane, butanedioldiglycidyl ether	Registered12
57834-33-0	ethyl 4-[[(methylphenylamino)methylene]amino]benzoate	Registered12
73038-25-2	Alcohol ethoxylate phosphate ester	Registered12
1065336-91-5	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.