(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 1 of 12

Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: FK 45 FOODGRADE Komponente B

ECHA-Registrierung 12/20 UFI: NQHF-CCHF-18SS-3UN6

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Industrial use Professional use Hardener for epoxy paint

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: Fakolith Farben GmbH

Address: Carl-Benz-Str. 19 City: D-64658 - Fürth/ Odw.

Province: Hesse

Telephone: +49 (0) 6253/ 2394-0
Fax: +49 (0) 6253/ 2394-10
E-mail: info@fakolith.com
Web: www.fakolith.com

'Information Department:

Germany: Uwe Farenkopf (germany@fakolith.com) Tel. + 49 (0) 6253 / 2394-0 Fax: +49 (0) 6253 / 2394-10

1.4 Emergency telephone number:

Spain: +34 (0) 915 620 420 **Germany:** +49 (0) 61 31 19 240 **Austria:** +43 (0) 14 06 43 43 **Switzerland:** +41 (0) 44 25 15 151 **Italy:** +39 (0) 26 44 42 523

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4: Harmful if swallowed.

Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Eye Dam. 1: Causes serious eye damage.

Skin Corr. 1B: Causes severe skin burns and eye damage.

Skin Sens. 1: May cause an allergic skin reaction.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020

Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:





Signal Word:

Danger

Hazard statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

P321 Specific treatment (see on this label).

Contains:

benzyl alcohol salicylic acid

Polycycloaliphatic Amine

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

The product may have the following additional risks:

Prevent material from contaminating groundwater. The product should not be allowed to enter drains, pipes, or soil (soil).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 3 of 12
Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

CAS No: 38294-64-3 EC No: 500-101-4	Polycycloaliphatic Amine	25 - 75 %	Aquatic Chronic 3, H412 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317	-
Index No: 603-057- 00-5 CAS No: 100-51-6 EC No: 202-859-9 Registration No: 01- 2119492630-38-XXXX	benzyl alcohol	22 - 50 %	Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302	-
Index No: 607-732- 00-5 CAS No: 69-72-7 EC No: 200-712-3 Registration No: 01- 2119486984-17-XXXX	salicylic acid	1 - 3 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Repr. 2, H361d	-
Index No: 603-064- 00-3 CAS No: 107-98-2 EC No: 203-539-1 Registration No: 01- 2119457435-35-XXXX	[1] 1-methoxy-2-propanol, monopropylene glycol methyl ether	1 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Print date: 15/06/2023

Version 1 Date of compilation: 4/12/2020

Version 2 (replaces version 1) Revision date: 29/03/2022

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 5 of 12
Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Use for direct food contact applications (Reg 10/2011)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³	
1-methoxy-2-propanol, monopropylene	107.00.2	European	Eight hours	100 (skin)	375 (skin)	
glycol methyl ether	107-98-2	107-98-2 Union [1]	Union [1]	Short term	150 (skin)	568 (skin)

[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
benzyl alcohol	DNEL	Inhalation, Chronic, Systemic effects	90
CAS No: 100-51-6	(Workers)		(mg/m³)
EC No: 202-859-9			
1-methoxy-2-propanol, monopropylene glycol methyl	DNEL	Inhalation, Chronic, Systemic effects	369
ether	(Workers)		(mg/m³)
CAS No: 107-98-2			
EC No: 203-539-1			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
	Industrial use
Uses:	Professional use
	Hardener for epoxy paint
Breathing protec	tion:
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 6 of 12
Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

A3+P3 Filter Type needed: Hand protection: Non-disposable protective gloves against chemicals. PPF: «CE» marking, category III. Check the list of chemicals for which the glove has been Characteristics: tested. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous Maintenance: than not using gloves, since the pollutant can gradually accumulate in the glove's material. They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could Observations: reduce their strength. Breakthrough time Material thickness 0,35 Material: PVC (polyvinyl chloride) > 480 (min.): (mm): Breakthrough time Material thickness Material: Nitrile > 480 0,38 (min.): (mm): Breakthrough time Material thickness Material: Chloroprene > 480 0,18 (min.): (mm): Eye protection: Protective goggles with built-in frame. «CE» marking, category II. Eye protector with built-in frame for protection against Characteristics: dust, smoke, fog and vapour. EN 165, EN 166, EN 167, EN 168 CEN standards: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance: be disinfected periodically following the manufacturer's instructions. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, Observations: scraping etc. Skin protection: Chemical protective clothing PPE: «CE» marking, category III. Clothing should fit properly. The level of protection Characteristics: must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material. EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034 CEN standards: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance: the manufacturer. The protective clothing's design should facilitate correct positioning, staying in place without moving for Observations: the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity. PPF: Anti-static safety footwear against chemicals. «CE» marking, category III. Check the list of chemicals against which the footwear Characteristics: is resistant. EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345 CEN standards: For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is Maintenance: observed. The footwear should be cleaned regularly and dried when damp, although it should not be placed too Observations:

close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Amber Odour: Amine

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 7 of 12 **Version 2 (replaces version 1)** Revision date: 29/03/2022 Print date: 15/06/2023

Boiling point or initial boiling point and boiling range: 208 °C (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: 77 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.) Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Insoluble

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: 0,075 (Estimation based on the indication of the Regulation (CE) No1272/2008.) Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1.05

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product

Explosive properties: Not applicable/Not available due to the nature/properties of the product Oxidizing properties: Not applicable/Not available due to the nature/properties of the product Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Print date: 15/06/2023

Version 1 Date of compilation: 4/12/2020

Version 2 (replaces version 1) Revision date: 29/03/2022

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

There are no tested data available on the product.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Oral) = 1.365 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1B: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 9 of 12
Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level	
benzyl alcohol	1.05			Manulani	
CAS No: 100-51-6 EC No: 202-8	59-9	-	-	Very low	
1-methoxy-2-propanol, monopropylene glyco		-	-	Very low	
CAS No: 107-98-2 EC No: 203-5	-0,44				

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

Waste classification according to the European Waste Catalogue:

08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 wastes from MFSU and removal of paint and varnish

08 01 99 wastes not otherwise specified

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Version 1 Date of compilation: 4/12/2020 Page 10 of 12 Version 2 (replaces version 1) Revision date: 29/03/2022 Print date: 15/06/2023

<u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN2735

14.2 UN proper shipping name.

Description:

ADR/RID: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS POLYCYCLOALIPHATIC AMINE), 8, PG III, (E) IMDG: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS POLYCYCLOALIPHATIC AMINE), 8, PG III ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS POLYCYCLOALIPHATIC AMINE), 8, PG III

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm - Emergency sheets (F - Fire, S - Spills): F-A,S-B

14.6 Special precautions for user.

Labels: 8



Hazard number: 80 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6. IMDG Code segregation group: 18 Alkalis

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end use such as floors, solvent-borne

Phase I* (from 01/01/2007): 550 g/l Phase II* (from 01/01/2010): 500 g/l

(*) g/l ready to use

VOC content (p/p): 35,761 % VOC content: 375,494 g/l

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Print date: 15/06/2023

Version 1 Date of compilation: 4/12/2020

Version 2 (replaces version 1) Revision date: 29/03/2022

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

.

Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4

Aquatic Chronic 3: Chronic effect to the aquatic environment, Category 3

Eye Dam. 1 : Serious eye damage, Category 1 Flam. Liq. 3 : Flammable liquid, Category 3 Repr. 2 : Reproductive toxicant, Category 2

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Skin Corr. 1B: Skin Corrosive, Category 1B Skin Sens. 1: Skin sensitiser, Category 1 Skin Sens. 1A: Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Elimination of ecological information values (SECTION 12.3).

(in accordance with Regulation (EU) 2020/878)

FK 45 FOODGRADE Component B



Print date: 15/06/2023

Version 1 Date of compilation: 4/12/2020
Version 2 (replaces version 1) Revision date: 29/03/2022

- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).

- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
38294-64-3	Polycycloaliphatic Amine	
100-51-6	benzyl alcohol	Registered12
69-72-7	salicylic acid	Registered12
107-98-2	1-methoxy-2-propanol, monopropylene glycol methyl ether	Registered12

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-continuea on next page.