


Type of material	Insulating spray white pigmented. For interior and exterior use.
Properties	<p>The insulating spray FAKOLITH FK 33 dries in a very short time even at low temperatures. This means that existing stains are not dissolved when wetted, but are immediately insulated by a thin film. Economical consumption due to fine spray head and thin layer application.</p> <ul style="list-style-type: none"> ■ Excellent insulating properties, even with difficult stains. <p>Can be recoated after only 10 min. drying (20°C / 60% relative humidity).</p> <p>Economical in use (thin-layer application).</p> <ul style="list-style-type: none"> ■ Optically perfect application due to fine spray head.
Areas of application	Isolates smoke, soot and nicotine stains, wax residues, grease and crayon stains as well as dried water marks.
Substrates	Mineral substrates, concrete, aqueous and solvent-based paints, plasterboard, wood, cardboard.
Substrate preparation	The substrate must be clean, dust-free and dry.
Processing	Application by spraying. Shake can well immediately before application. Spray a thin layer of FAKOLITH FK 33 Insulating Spray onto the surface in a cross-coat pattern. Distance approx. 20-25 cm.
Binder	Acrylic polymer
Overpaintability	With emulsion paints and solvent-based 1K coatings
VOC content	Does not apply to spray cans.
Pigmentation	Titanium dioxide
Density at 25°C	0.79 g/cm ³
Flash point	-44.5 °C (propane)
Gloss level	Silk matt
Colour shade	White
Tinting	Not foreseen
Consumption	Approx. 100 ml/m ² , depending on the absorbency of the substrate.
Drying time	Can be recoated after only approx. 10 minutes (+20°C/60% rel. humidity. The ambient temperature determines the drying time).
Application temperature	From 0°C for circulating air and object
Compatibility	Do not mix with other products
Storage	Approx. 2 years, store in a cool and frost-free place.
Container	400 ml (aerosol spray can). Packaging unit: 12 x 400 ml in a carton
Occupational safety	For proper handling, read the safety data sheet, use your personal protective equipment and take the prescribed measures.

Disposal	Only recycle completely empty containers. Dispose of non-empty containers in accordance with local regulations.
Note	Pressurized container, protect from heat above 50°C and sunlight. Do not spray on flames or incandescent bodies. Do not open by force or burn after use. Do not spray into eyes or onto inflamed skin. Please observe the safety data sheet.
Safety datasheet	 <p>Sicherheitsdatenblatt FAKOLITH FK 33</p>

LEGAL NOTICE:

The companies FAKOLITH Farben GmbH and FAKOLITH Chemical Systems S.L.U. are certified according to the quality management system DIN EN ISO 9001:2015 by TÜV Rheinland Cert, Cert. No. 01100071679/01.



This technical information and recommendation regarding the processing and use of the product is based on our current knowledge and experience using standard situations and the use of the product within its shelf life. This information does not release the buyer and/or user from the obligation to determine whether our offer, recommendation or the technical quality and characteristics of our products meet their specific requirements. FAKOLITH reserves the right to update the characteristics and specifications of the products. Updated editions will be published at www.fakolith.de. An updated edition of this document invalidates the previous version (see date of creation).

Technical information 12.10.2021FE